


Extension power supply modules

FX3S FX3G FX3GC FX3GE FX3U FX3UC FX5U FX5UC



The power supply module FX5-1PSU-5V is used when the FX5U (AC power supply type) CPU module's internal power supply is insufficient. Up to two FX5-1PSU-5V units can be used for one system.

The power supply module FX5-C1PS-5V is required when the built-in power supply is

insufficient in the FX5U (DC power type) and FX5UC CPU modules. When connecting a module of extension cable type to a FX5UC CPU module, the FX5-C1PS-5V also acts as a connector conversion module. Up to two FX5-C1PS-5V units can be used for one system.

Specifications	FX5-1PSU-5V	FX5-C1PS-5V
Application	Power supply for FX5U (AC power supply type)	Power supply for FX5U (DC power supply type) and FX5UC
Rated power supply voltage	100–240 V AC (50/60 Hz)	24 V DC
Power consumption	Max. 20 W	Max. 30 W
Output voltage	5 V DC/24 V DC	5 V DC/24 V DC
Max. output current	5 V DC	1.2 A at 40 °C; 0.8 A at 55 °C
	24 V DC	0.3 A at 40 °C; 0.2 A at 55 °C
No. of connectable modules		1.2 A at 40 °C; 0.8 A at 55 °C
		0.625 A at 40 °C; 0.4 A at 55 °C
No. of connectable modules	Max. 2	Max. 2
Related I/O points	0	0
Weight	kg 0.3	0.1
Dimensions (WxHxD)	mm 50x90x83	20.1x90x74
Order information	Art. no. 280509	294586

SD memory card

FX3S FX3G FX3GC FX3GE FX3U FX3UC FX5U FX5UC




The built-in SD memory card slot can be used for data logging and convenient program update.

Specifications	SDHC CARD 8GB
Memory type	SDHC
Memory capacity	8 GB
Order information	Art. no. 306787

Backup batteries

FX3S FX3G FX3GC FX3GE FX3U FX3UC FX5U FX5UC



FX3U-32BL

Batteries

The battery buffers the internal RAM of the MELSEC PLC in the event of a voltage failure.

The battery FX3U-32BL can be used for all base units of the MELSEC FX3G/FX3GC/FX3GE/FX3U/FX3UC/FX5U/FX5UC series.

Specifications	FX2NC-32BL	FX3U-32BL
Applicable for	FX2N-20GM module	Base units FX3G/FX3GC/FX3GE/FX3U/FX3UC/FX5U/FX5UC
Order information	Art. no. 128725	165286