



Facts

General description

Part number	640009505
Life cycle status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC
Safety	UL 61010-1, UL 61010-2-201, CAN/CSA-C22.2 No. 61010-1, CAN/CSA-C22.2 No. 61010-2-201

Mechanical

Mechanical size	556 x 347 x 65mm
Mounting option	Panel Mount, VESA 75 x 75
Number of touches	1 million finger touch operations
Touch type	Resistive
Cut-out size	539 x 331mm
Weight	7.38 kg
Housing material	Powder-coated aluminum, Gray

Power

Input voltage	24 V DC (18 to 32 VDC)CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supply must conform with the requirements for class II power supplies.
Power consumption (max)	45.6W
Input fuse	Internal DC fuse

System

CPU	i.MX6Quad, Quad ARM Cortex-A9 1.0GHz 1MBL2cache
RAM	2 GB
FLASH	2GB SSD(eMMC), 1.5GB free for application

Display

Size diagonal	21.5" diagonal
Resolution	1920x1080 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	250 cd/m2
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

Smart Engineering Resources

X2 pro 21

21" HMI with iX runtime

Full 1920 × 1080 pixel HD resolution (16:9)
TFT-LCD touch screen
1.5 GB application memory
Ethernet 2x100 Mbit
0°C to +50°C operating temperature
CE, FCC, KCC, UL approvals

Digital IO

Digital output	2xDO Solid state relay, 0.5A@24VDC
----------------	------------------------------------

Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS485 (only if COM 2 is RS485)

Ethernet communication

Number of Ethernet ports	2
Ethernet port 1	1x10/100 Base-T (shielded RJ45)
Ethernet port 2	1x10/100 Base-T (shielded RJ45)

Communication CAN

Number of CAN ports	2
CAN port 1	0.5 MBit
CAN port 2	0.5 MBit

Expansion interface

Expansion port	Yes, ciX expansion module
SD card	SD and SDHC
USB	2xUSB 2.0 500mA

Environmental

Operating temperature	0°C to +50°C
Storage temperature	-20°C to +60°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65, NEMA 4X/ 12 and UL 50E Type 4X/ 12
Sealing back	IP20
Humidity	5% - 85% non-condensed
Altitude (max)	< 3000m