


## Sockets

### KUN 10



Product	KUN 10
description	Insulated coupling for a 4 mm diameter plug and screw connection up to cable cross-section of 1.5 mm <sup>2</sup> . Tin-plated brass socket. The socket is screwed into the insulated handle.
article-no. / *colour	9301891xx <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  00 black         </div> <div style="text-align: center;">  01 red         </div> </div> <div style="text-align: right; border: 1px solid black; padding: 2px; width: fit-content; margin-left: auto;">Sn</div>
drawing	
	
technical data	
connection	screw terminal
rated voltage <sup>(1)</sup>	30 VAC / 60 VDC
measurement cat. acc. to IEC 61010	O <sup>(3)</sup>
rated current <sup>(1)</sup> (consider derating curve)	16 A
material socket	brass, tin plated
housing material	PS
temperature range acc. To IEC61010 <sup>(2)</sup>	-25 °C to +70 °C
flammability class acc. to UL 94 (only valid for basic material of housing)	HB
standard	IEC 61010

4 mm system

<sup>(1)</sup> for normal environmental conditions -5°C to +40°C

<sup>(2)</sup> contact the manufacturer for applications at deviating temperature ranges

<sup>(3)</sup> Other circuits that are not directly connected to mains

stand: 30.07.2018