

Data sheet

GSA 3000 N schwarz/black - GSA 3000 N schwarz/black

Industrial Connectors:Rectangular connectors GDM-series:Type A EN 175301-803 (DIN 43650) / ISO 4400:Appliance connector:GSA 3000 N schwarz/black

Name GSA 3000 N schwarz/black



Delivery informations

Document created at 16-07-2010
Availability available

Product description

Description appliance connector with retaining nut, 2 screws M 3 x 10 and 1 screw M 3 x 5, open nut
Type GSA 3000 N schwarz/black
Order No. 932 968-100
Number of contacts 3 + PE
Standard DIN EN 175 301-803-A
Housing Color black
Construction type A

Technical data

Rated voltage AC/DC 400 V
Rated current 16 A
Contact resistance $\leq 4 \text{ m}\Omega$
Type of termination solder (ground contacts: screw)
Mounting screw

Material

Contact surface material Sn
Contact bearer material PA
Housing material PA

Environmental conditions

Protection class (IEC 60529) IP 65 (gasket necessary) (mated)
Pollution severity 3
Temperature range -40 °C to +125 °C

Inflammability class

Contact bearer 94 V-0

Approvals

UR UR
VDE VDE
SEV SEV
CSA CSA

Packing unit

Packaging unit 200 pieces

Scope of delivery and accessories

Accessories to order separately (NBR) flat gasket GSA 200-4, Order no. 730 843-002; (EPDM) flat gasket GSA 200-7, Order no. 730 268-003

Industrial Connectors:Rectangular connectors GDM-series:Type A EN 175301-803 (DIN 43650) / ISO 4400:Appliance connector:GSA 3000 N schwarz/black

Picture

Drawing

